

PRODUCT OVERVIEW

Fibre Optic Cable Installation Machines



ACCU



110/230 V



110/230 V

Model	PetitBlown	SmallBlown 1	SmallBlown 2
Typical Usage	Inside	Inside	Inside
Fiber/Cable OD	0.8 - 3 mm	0.8 - 6.5 mm	0.8 - 6.5 mm
Duct Size OD	3 - 10 mm	5 - 16 mm	5 - 16 mm
Part no. #			
Max Speed	150 m/min (490 ft)	90 m/min (295 ft)	90 m/min (295 ft)
Blowing distance	Up to 1200 m (3940 ft)	Up to 2500 m (8200 ft)	Up to 2500 m (8200 ft)
Rec. Airflow	0-500 l/min (0-17.7 cfm)	200-500 l/min (7.1-17.7 cfm)	200-500 l/min (7.1-17.7 cfm)
Rec. Pressure	0-10 bar air (0-150 psi)	8-16 bar air (120-230 psi)	8-16 bar air (120-230 psi)
Service requirement	Annually	Annually or every 350000 m	Annually or every 350000 m
Length Width Height Weight	212 mm 104 mm 139 mm 2.8 kg (w/o battery)	Machine: 250 mm 150 mm 220 mm 9.7 kg Control Box: 200 mm 150 mm 80 mm 1.9 kg	Machine: 250 mm 150 mm 220 mm 11.3 kg Control Box: 240 mm 250 mm 80 mm 1.9 kg
Unique features	- Fully automatic - Unique double fiber protection - Battery-powered - No tool needed - Easy load and removal of pre-connected products - Easy-to-read LED display - Multiple positions - Lightweight but powerful	- Auto-Buckle Detection - Adjustable Torque - Preset Automatic Stop - Adjustable Speed Control - Speed, Torque & Count Display - Air Pressure & Flow Regulation - Easy to Operate - Simple Maintenance	- Software operated - Electronic Hardware - Modern Connectivity - Verification of job quality - Auto-buckle Detection - Adjustable Torque - Preset Automatic Stop - Adjustable Speed Control

PRODUCT OVERVIEW

Fibre Optic Cable Installation Machines



HYDRAULIC



HYDRAULIC



HYDRAULIC

Model	FastBlown	PowerfulBlown	VariousFlow
Typical Usage	Outside	Outside	Outside
Fibre/Cable OD	3 - 12 mm	8 - 25 mm	8 - 32 mm
Duct Size OD	7 - 20 mm	18 - 70 mm	18 - 70 mm
Part no. #			
Max Speed	100 m/min (325 ft)	80 m/min (260 ft)	80 m/min (260 ft)
Pushing Force	0-40 kg	0-125 kg	0-200 kg
Blowing distance	Up to 3500 m (11485 ft)	Up to 10000 m* (32810 ft)	Up to 10000 m* (32810 ft)
Rec. Airflow	1000 l/min (35.3 cfm)	8000-12000 l/min (282.5 - 423.8 cfm)	8000-12000 l/min (282.5 - 423.8 cfm)
Rec. Pressure	8-16 bar air (120-230 psi)	8-12 bar air (120-170 psi)	8-12 bar air (120-170 psi)
Service requirement	Annually	Annually	Annually
Length	650 mm	650 mm	700 mm
Width	225 mm	230 mm	230 mm
Height	210 mm	350 mm	350 mm
Weight	24 kg	38 kg	40 kg
Unique features	• Use with Air or Water* • Push Force Monitor • Rugged Construction • Flexible Adaptability • Adjustable Torque • Distance and Speed measurment • Ease of Use • Simple Maintenance	• Use with Air or Water* • Only for Single Cable • Rugged Construction • Flexible Adaptability • Adjustable Torque • Distance and Speed measurment • Ease of Use • Simple Maintenance	• Use with Air or Water* • Relining or Single Cable • Rugged Construction • Flexible Adaptability • Adjustable Torque • Distance and Speed measurment • Ease of Use • Simple Maintenance