



Product Description

The Briticom® ACx anchor clamps are used for the dead-ending of aerial figure-8 cables or aerial figure-8 duct structures with steel messenger deployed on overhead access networks where spans do not exceed 90m. These anchor clamps are made of an open conical body, a pair of metallic jaws and a flexible bail. Parts are secured all together to prevent any loss. The automatic conical cable clamping does not require any installation tool or any prior cable preparation. When tightening, the jaws perforate the messenger’s sheath and anchor on the steel part.

Features & Benefits

- Simple, fast and toolless installation
- Installation on different types of pole hardware, eye or pigtail 15mm min
- Effective cable clamping by conical wedging

Applications

- On end poles
- When the line is at an angle greater than 25°, in order to preserve the integrity of the cable.
- If road crossing
- In case of unbalanced adjacent spans
- If a rugged terrain
- In alignment, every 5 poles or on every pole

Technical Specifications

Model	Ø Messenger	Bail Length	Material			Maximum Load Tension	Weight	Packaging
			Body	Jaws	Bail			
AC6 140	3-6mm	140mm	Thermoplastic	Zinc alloy	Stainless steel	1000 N	0.09kg	100 units
AC6 260		260mm						
AC7 200	4-7mm	200mm	Aluminum alloy					
AC7 260		260mm						
AC7 500		500mm						
AC10 260	6-8mm	260mm				5000 N	0.3kg	50 units
AC10 500		500mm						

To Order

To place an order, use the contact details below.

