





Fibre Optic Cable

ADSS Double Jacket Multi-Tube Aerial Cable



Technical Specifications

Outer Sheath	PE or LSZH
Fibre Count	12 to 432
Outer Diameter (mm)	12.7 ~ 25.0
Weight per Km	119kg ~ 474kg
Max Tensile Strength (N)	10731 ~ 30207
Operating Temp. (°C)	-40 ~ 70

To Order

Ordering information on page 2.

Product Description

Briticom® offers a wide range of indoor and outdoor fibre optic distribution, patching and consumer cables including Plenum, Riser and LSZH in all diameters. These are used to provide links to protocols such as FTTH, FDDI, 10 Gigabit Ethernet, ATM.

Features & Benefits

- ADSS Aerial Cable – Multi Tube
- Double Jacket
- High tensile strength
- For outdoor aerial use
- Water, flame and rodent resistant
- Available in many colours

Applications

- Telecommunication networks
- CATV - Cable television
- Fibre-To-The-Home (FTTH)





Fibre Optic Cable

ADSS Double Jacket Multi-Tube Aerial Cable

Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

Cable Type		Fibre Type		No of Fibres		Span	
ADSS	ADSS	S1	OS1	1	1 F0	50	50m
F8FR	Figure 8 with FRP	S2	OS2	2	2 F0	80	80m
STA	Steel Tape Armoured	M1	OM1	4	4 F0	200	200m
F8SM	Fig-8 with Steel Messenger	M2	OM2	6	6 F0	600	600m
		M3	OM3	7	7 F0		
		M4	OM4	9	9 F0		
		A1	G657A1	10	10 F0		
		B3	G657B3	12	12 F0		
		A2	G657A2	24	24 F0		
				72	24 F0		
				48	48 F0		
				96	96 F0		
				144	144 F0		
				288	288 F0		
▲		▲		▲		▲	
ADSS	MT	S2	DJ	72	PE	150	
▼		▼		▼			
Single Tube	ST	Single Jacket	SJ	HDPE	HD		
Multi Tube	MT	Double Jacket	DJ	PVC	PV		
				LSZH	LS		
				Polyethylene	PE		
				LDPE	LD		
				Double Jacket PE/ PVC	DJ		
				Double Jacket HDPE	DJHD		
				Single Jacket HDPE	SJHD		
				Single Jacket PE	SJPE		
Tube		No of Jackets		Material			

*Leave blank if not required

Example Part Number	
Description	Part Number
Multi Tube ADSS Aerial Cable 72 F0 Single-mode OS2 Double Jacket PE – 150m Span	ADSSMTS2DJ72PE150

To Order

To place an order, use the contact details below.