



Cable Management

Cable Trailer

Product Description

The Briticom® Cable Trailer is used for efficient and reliable loading, transportation and unreeling of fibre optic or copper structured cables from drums. All our cable trailers are road-going and suitable for use on site. They are fitted with a hydraulic hand pump operated lift and lower system as a standard, which, when fully raised, mechanically locks to ensure drum security in transit.

Features & Benefits

- High quality welded steel frame with anti-corrosion (hot-dip galvanisation)
- Hydraulic hand pump
- Safe and easy drum handling
- Fully road compliant, and suitable for site use
- Lights of EEC Standard
- Reliable braking system with automatic reversing
- Sturdy wheels and tires

Applications

- Telecommunication networks
- CATV – Cable television



Technical Specifications

Frame	Steel, welded, hot-dip galvanized
Brakes	Chassis AL-KO KOBER 2700kg, mechanical overrun brakes with automatic reversing
Tire Dimensions	185R14C
Track Width	1790 mm
Hook	AL-KO AK301 3000kg (AK 350 also available)
Recommended Wheel Pressure	66 PSI

Ball Coupling Specifications

	AK 301	AK 350
Weight Range	≤ 3000kg	≤ 3500kg
Max. Trailer Load on Coupling	325kg	350kg
Pipe Diameter	50mm	60mm

To Order

To place an order, use the contact details below.



Model Specifications

Model	Drum Dimensions	DMC	Weight	Tire Dimensions
1	120 x 200 cm	950 – 2700 kg	500 kg	185R14C
2	130 x 200 cm	950 – 2700 kg	510 kg	185R14C
3	150 x 270 cm	950 – 2700 kg	530 kg	185R14C
4	175 x 270 cm	950 – 2700 kg	550 kg	185R14C

Example Part Number	
Description	Part Number
Cable Trailer 2700kg DMC Capacity 175 X 270cm	P3500D4TRA

To Order

To place an order, use the contact details below.