



Product Description

Briticom® provides this high performance Launch Cable Box with interchangeable SC/FC/ST adapters in UPC or APC polishing end face. It is used to aid in the testing of fibre optic cable when using an OTDR. The OTDR Launch Cable Box is used with Optical Time Domain Reflectometres (OTDRs) to help minimise the effects of the OTDR's launch pulse on measurement uncertainty.

Features & Benefits

- Compact, easy to carry
- Compound latch for positive seal and easy opening with locking feature
- Water- and dust-proof allowing the unit to be taken into almost any environment
- Case can house up to 1000 metres of fibre

Applications

- Training and calibration
- Installation and testing by OTDR

Technical Specifications

Fibre Type	SM G.652D
Adapter Type	Interchangeable FC/SC/ST adapters
Typical Loss	<0.5dB @ 1310nm for 1km
Material	SR Polypropylene
Polishing Type	APC/UPC selectable
Color	Black
Dimension (mm)	206(L) x 122(W) x 23(H)
Weight	1kg

To Order

To place an order, use the contact details below.





Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

Port A		Coating		Fibre Type		DZE	
ST	ST	A	Angled	A1	G657A1	DZE	Dead Zone
SC	SC	U	Uncoated	A2	G657A2		Eliminator
MU	MU			B3	G657B3		
LC	LC			S2	OS2		
FC	FC			M1	OM1		
E2	E2000			M2	OM2		
				M3	OM3		
				M4	OM4		
				M5	OM5		
▲		▲		▲		▲	
SC	SC	A	2	S2	C	DZE	500
	▼		▼		▼		▼
ST	ST	2 Ports	2	Compact Plastic	C	150m	150
SC	SC			Waterproof	W	1000m	1K
MU	MU			Ring-Type	R	2000m	2K
LC	LC			Compact Aluminium	A	3000m	3K
FC	FC			Large Plastic	L	4000m	4K
E2000	E2						
Port B		Adapter Ports		Box Type		Length of Fibre	

Example Part Number	
Description	Part Number
Compact OTDR Launch Leads (DZE) - Plastic Box SC-SC APC 2 Ports - OS2 500m	SCSCA2S2CDZE500

To Order

To place an order, use the contact details below.