



Technical Specifications

|                          |                                    |
|--------------------------|------------------------------------|
| Fibre Stripping Stations | Jacket, 900 micron, and 250 micron |
| Weight (g)               | 79                                 |
| Dimensions (mm)          | 29.7 x 55.6 x 103.6                |

Product Description

This MILLER® Fibre Optic Centre Feed Stripper is a fibre stripper with a centre feed design which allows for a longitudinal approach of fibre stripping. The fibre is fully supported in the stripping process of 900-micron buffer coating to 250-micron and standard 250-micron coating to 125-micron stripping.

Features & Benefits

- Measurement scale in inches/mm built into the tool jaw and body up to 2 3/4 in. (70 mm) for ease of proper cable preparation
- Compact, lightweight and ergonomically designed for ease of use
- All cutting surfaces are precision formed, hardened, tempered and ground assuring precise cable jacket, buffer and acrylate removal with no scratching or nicking of the fibre
- Removable cleaning brush is conveniently attached to the stripper for periodic cleaning of stripping jaws
- Supplied with its own individual protective polymer tool case for clean and safe storage
- Side mounted stripper blades provide convenient stripping of 1.6 mm to 3 mm cable jackets

Applications

- Fibre optic preparation and termination

To Order

To place an order, use the contact details below.





Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

| Use                        |                        | Cable Diameter          |                          | Brand*                        |                                     |
|----------------------------|------------------------|-------------------------|--------------------------|-------------------------------|-------------------------------------|
| <b>FTTH</b>                | FTTH                   | <b>32</b><br><b>1T3</b> | 3x2mm<br>125µm to 3mm    | <b>ML</b>                     | MILLER®                             |
| ▲                          |                        | ▲                       |                          | ▲                             |                                     |
| <b>FTTH</b>                | <b>FC</b>              | <b>1T3</b>              | <b>YEL</b>               | <b>ML</b>                     | <b>M1</b>                           |
| ▼                          |                        | ▼                       |                          | ▼                             |                                     |
| Drop Cable<br>Feeder Cable | <b>DC</b><br><b>FC</b> | Black<br>Yellow         | <b>BLK</b><br><b>YEL</b> | Model 1<br>Model 2<br>Model 3 | <b>M1</b><br><b>M2</b><br><b>M3</b> |
| Product                    |                        | Colour                  |                          | Model                         |                                     |

\*Leave column blank if unbranded

| Example Part Number                                                             |                  |
|---------------------------------------------------------------------------------|------------------|
| Description                                                                     | Part Number      |
| Fibre Optic Centre Feed Longitudinal Stripping Tool 1.6~3mm Cable 250 and 900µm | FTTHFC1T3YELMLM1 |

To Order

To place an order, use the contact details below.