



Fibre Optic Cable

Horizontal Armoured Dielectric Multi Loose Tube Cable



Product Description

Briticom® offers a wide range of indoor and outdoor fibre optic distribution, patching and consumer cables including Plenum, Riser and LSZH in all diameters. These are used to provide links to protocols such as FTTH, FDDI, 10 Gigabit Ethernet, ATM.

Features & Benefits

- For outdoor or indoor use
- PE and flame-retardant LSZH sheath options
- Harsh environments including direct burial
- Multi-tube structure

Applications

- FTTH
- Telecom
- Indoor/Outdoor datacomms



Technical Specifications

Fibre Count	4 ~ 144
Outer Sheath	PE, LSZH, PVC, Plenum
Outer Diameter (mm)	11.4 ~ 15.8
Nominal Weight (kg/km)	98.5 ~ 180
Short - Max Tensile Strength (N)	~ 3500
Min Bend Radius (mm)	112 ~ 158
Max Crush Resistance (N/100mm ²)	2500
Operating Temperature (°C)	-35 to +70

To Order

Ordering information on page 2.





Horizontal Armoured Dielectric Multi Loose Tube Cable

Use combinations of **bold** letters and numbers to create part numbers for ordering.

*Leave blank if not required

To Order

To place an order, use the contact details below.