



Fibre Management

Outdoor Combined Use AC Pole Fibre Cabinet – Model O3



Product Description

Briticom® fibre optic outdoor cabinets and frames are used to house and protect fibre optic cables for pass-through, reservation and fibre distribution.

Features & Benefits

- This is a fully customisable cabinet – various sizes, configurations and accessories available
- IP65 and IK10 rating (harsh environment and temperatures)
- Max capacity 574 FO
- Three-point pad lockable door mechanisms
- Allows quick installation of fibre optic cable
- RoHS compliant materials
- Lockable door

Applications

- Telecommunication networks
- LAN, MAN and WAN applications
- Military Installation
- CATV - Cable television



Technical Specifications

Material	Cold-rolled steel (electrostatic sprayed), glass reinforced plastic (SMC)
Heights Available (mm)	1000, 1250, 1500, 1750, 2000, 2200
Depths Available (mm)	600, 800, 900
Width (mm)	800
IP Rating	IP65
Operating Temperature	-40 to +60°C
Refrigerant	R134a
Noise Level	65dB(A)
Cooling/Heating Capacity	1500W/1000W
Internal Airflow	M3/h 350

To Order

Ordering information on page 2.





Fibre Management

Outdoor Combined Use AC Pole Fibre Cabinet – Model 03

Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

Model		Fibres		Rating		Colour	
01	Outdoor Model 1	288	288 FO	I55	IP55	K	Black
02	Outdoor Model 2	512	512 FO	I65	IP65	B	Beige
03	Outdoor Model 3	574	574 FO			G	Grey
01A	Outdoor Model 1A						
02B	Outdoor Model 2B						
04	Outdoor Model 4						
05	Outdoor Model 5						
06	Outdoor Model 6						
▲		▲		▲		▲	
03	FPC	574	SD	I65	86	G	
	▼		▼		▼		
Fibre Distribution Frame	FDF	Double Doors	DD	800x600	86		
Fibre Street Cabinet	FSC	Single Door	SD	800x800	88		
Fibre Pole Cabinet	FPC			800x900	89		
Product		Doors		Size			

Example Part Number	
Description	Part Number
Outdoor Combined Use AC Pole Single Door Fibre Cabinet 574 Fibres – IP65 800x600 Model 03 – Grey	03FPC574SDI6586G

To Order

To place an order, use the contact details below.