



Fibre Management



Product Description

Briticom® fibre optic distribution and termination boxes are used for the easy-access and distribution of fibre optic connections between networks.

Features & Benefits

- UV resistant
- 36 FO
- Max 3 splice trays (12 FO each)
- 4 + 2 cable entries
- RoHS compliant materials
- Lockable door
- IP65 for outdoor installations

Applications

- Telecommunication networks
- LAN, MAN and WAN applications
- CATV - Cable television
- Fibre-to-the-Home (FTTH)

Technical Specifications

Material	SPCC cold-rolled steel
Dimensions	420x380x126.3mm
Max Capacity	36
Max Splice Tray Quantity	3pcs
Max Splice Tray Capacity	12 fibres
IP Rating	IP65
Cable Entries	4 + 2 @ Φ 10 ~ 18mm

To Order

Ordering information on page 2.





Fibre Management

Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

Product (Box)		Material		Polish Type*		No of Fibres	
ITB	Indoor Terminal	P	Plastic	A	APC	01	1 Pieces
IDB	Indoor Distribution	M	Metal	U	UPC	02	2 Pieces
OTB	Outdoor Terminal					04	4 Pieces
ODB	Outdoor Distribution					06	6 Pieces
ISB	Indoor Splitter Box					08	8 Pieces
OSB	Outdoor Splitter Box					09	9 Pieces
DRB	DIN Rail Box						
⬆		⬆		⬆		⬆	
ODB	08	M	SC	U	SX	36	
⬇		⬇		⬇		⬇	
Model 1	01	SC	SC	Duplex	DX	Pigtails	/P
Model 2	02	E2000	E2	Quad	QD		
Model 3	03	MTP	MTP	Simplex	SX		
Model 4	04	FC	FC				
Model 5	05	ST	ST				
Model 6	06						
Model 7	07						
Model 8	08						
Model 9	09						
Model		Adapter Type		Capacity		Additional	

*Leave column blank if unloaded.

Example Part Number	
Description	Part Number
Outdoor SC UPC Simplex 36 FO Splicing Distribution Box – Metal – Model 08	ODB08MSCUSX36

To Order

To place an order, use the contact details below.