



Fibre Management

Outdoor Street Fibre Cabinet – Model 01B



Technical Specifications

Material	Cold-rolled steel (electrostatic sprayed), glass reinforced plastic (SMC)
IP Rating	IP65
Dimensions	1450(H) x 1300(W) x 400(D)mm
Adapter Port	SC simplex
Max Capacity	576 core (SC adapter)
Max Splice Tray Qty	48 Pcs
Max Splice Tray Capacity	12 Fibres
Splitter	16pcs PLC splitter (cassette type)
Cable Port Diameter	Φ30mm

Product Description

Briticom® fibre optic outdoor cabinets and frames are used to house and protect fibre optic cables for pass-through, reservation and fibre distribution.

Features & Benefits

- IP65 and IK10 rating (harsh environment and temperatures)
- Max capacity 576 FO (SC)
- Allows quick installation of fibre optic cable
- Capacity can be adjusted as necessary
- Built-in direct splice unit
- RoHS compliant materials

Applications

- Telecommunication networks
- LAN, MAN and WAN applications
- CATV - Cable television
- Fibre-to-the-Home (FTTH)



To Order

Ordering information on page 2.





Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

Model		Fibres		Rating		Colour	
01	Outdoor Model 1	192	192 FO	I55	IP55	K	Black
02	Outdoor Model 2	288	288 FO	I65	IP65	B	Beige
03	Outdoor Model 3	512	512 FO			G	Grey
01A	Outdoor Model 1A	576	576 FO				
02B	Outdoor Model 2B						
04	Outdoor Model 4						
05	Outdoor Model 5						
06	Outdoor Model 6						
▲		▲		▲		▲	
01B	FSC	576	DD	I65	134	G	
▼		▼		▼			
Fibre Distribution Frame	FDF	Double Doors	DD	1300x400	134		
Fibre Street Cabinet	FSC	Single Door	SD	750x600	76		
Fibre Pole Cabinet	FPC						
Product		Doors		Size			

Example Part Number	
Description	Part Number
Outdoor Street Fibre Cabinet 576 Fibres – Double Doors IP65 1300x400 – Model 01B Grey	01BFSC576DDI65134G

To Order

To place an order, use the contact details below.