



Product Description

Briticom® HDPE/PEHD tubes can be used to protect fibre optic cabling. They have age resistance, high insulation, corrosion resistance, high weather resistance, excellent flame resistance and are flexible so can be easily manipulated to avoid obstacles.

Features & Benefits

- Strong and safe direct burial installation
- High insulation
- HDPE/PEHD materials
- Flame retardant self-extinguishing
- Corrosion resistant

Applications

- Telecommunication networks
- CATV – Cable television



Technical Specifications

Standards & Norms	GB/ T13663-2000/ISO4427
Outer Diameter	O.D.40mm (40mm-40.8mm), Thickness of tube 3.7mm-3.72mm
Materials	HDPE (PEHD)
Oxidation Induction Time 200°C	≥10
Elongation at Break %	≥350

To Order

To place an order, use the contact details below.



Ordering Information

Use combinations of **bold** letters and numbers to create part numbers for ordering.

Product		Diameter (mm)		Colour	
PV	PVC Pipe	20	20mm	BLK	Black
HD	HDPE Pipe	25	25mm	ORN	Orange
SS	Stainless Steel	32	32mm	BLU	Blue
		38	38mm	GRY	Grey
		40	40 mm		
		42	42mm		
		45	45mm		
		51	51mm		
▲		▲		▲	
HD	NC	40	50	ORN	
▼		▼			
Galvanised	GV	1m	1		
Non-Galvanised	NG	2m	2		
PVC	PV	5m	5		
Galvanised with PVC Coating	GP	6m	6		
No Coating	NC	10m	10		
		20m	20		
		50m	50		
		100m	100		
Coating		Length (m)			

Example Part Number	
Description	Part Number
HDPE Pipe 40mm Diameter – 50m – Orange	HDNC4050ORN

To Order

To place an order, use the contact details below.