

Aerial Fitting Accessories

Subscriber Connection Clamp



Product Description

The Briticom® fiber drop wire clamp is composed of a body, a wedge and a shim. A solid wire bail is crimped to the wedge. All parts are made out of stainless steel. Briticom® offer this tension clamp with appropriate dead-end anchor FTTH ODWAC clamp, S-type, ACC and other FTTH clamps. All the assemblies passed the tensile tests, operation experience with temperatures ranging from -60 °C up to +60 °C test, temperature-cycling test.

As one of the professional fiber optic accessories suppliers, Briticom® can customize the optical cable according to your requirements.

Features & Benefits

- Fiber Diameter range of fiber optic clamps: 3-7mm;
- Good corrosion resistant, durable and economical;
- Made of stainless steel;
- Use with HC, YK, ODWAC-22 and hoop;
- Consists of three parts: a shell, a shim and a wedge equipped with a bail wire.

Applications

- Aerial cabling

Technical Specifications

Length	220mm
Outer Material	Stainless Steel 201/304/430
Thickness of outer sheath	0.78mm
Tensile Strength	450N
Cable Diameter	3-7mm
Insert Material	Stainless Steel 201/304/430/PP
Thickness of insert	0.45mm
Weight	44.5g
Part Number	ODWAC- 22

To Order

To place an order, use the contact details below.

